

SASO 2884: 2017 ENERGY EFFICIENCY INFORMATION



A.O. Smith Brand Model Number	Declared Load Profile	Energy Efficiency Class	Bar Color	Rated Energy Efficiency %	Rated Annual Electricity Consumption (kWh/year)	Thermostat Temperature Setting (Celcius)	Rated Capacity (Liters)		Rated Voltage Range	Rated Frequency (Hz)	Rated Power Input (kW)	Rated Current (amps) (at 230V)	Rated Mixed Qty of Water/V40 (Liters)
ECT-52X 310	XL	E	Orange	91.6	4620	60°C	170		220-240	50/60	4.5	19.56	228
ECT-55X 310	XL	D	Yellow	94	5775	60°C	205		220-240	50/60	4.5	19.56	279
ECT-66X 310	XL	E	Orange	91	5985	60°C	225		220-240	50/60	4.5	19.56	291
ECT-80X 310	2XL	E	Orange	92.6	5875	60°C	275		220-240	50/60	4.5	19.56	354
ECT-120X 310	3XL	D	Yellow	95.6	10805	60°C	400		220-240	50/60	4.5	19.56	524
ECS-30X 310	L	D	Yellow	90	2875	60°C	100		220-240	50/60	4.5	19.56	139
ECS-40X 310	L	D	Yellow	90.3	2870	60°C	135		220-240	50/60	4.5	19.56	180
EJC-6 310	S	F	Red	64.5	740	60°C	20		220-240	50/60	1.5	6.52	30
EJC-10 310	S	F	Red	65.2	730	60°C	30		220-240	50/60	1.5	6.52	42
EJCS-20 310	M	F	Red	80.7	1690	60°C	65		220-240	50/60	2.5	10.87	88
EJCS-20-030 310	M	F	Red	77.3	1700	60°C	65		220-240	50/60	3.0	13.04	81
EJCT-20 310	M	E	Orange	83.1	1575	60°C	65		220-240	50/60	2.5	10.87	98

NOTICE: Pipe Insulation is included inside the packaging of the unit, and must be installed on the cold water inlet and hot water outlet piping during installation.

NOTICE: Keep this insert sheet with the water heaters manual for you or future users.