



## Quick Connect Series

### Water Treatment Filtration Systems

Make filtered water your secret ingredient with high performance water filtration for foodservice.

- Combine our filter cartridges to improve the taste and quality of your water by reducing harmful contaminants, sediments and/or scale.
- Designed for high volume and high demand.
- Filtration down to 0.5 microns
- Easy to use and maintain
- Tested by NSF for the reduction of chlorine taste and odor.
- Pressure Requirements: 10 – 125 psi (0.7 – 8.6 bar), non-shock
- Temperature: 35 - 100°F (2 - 38°C)
- No electrical connection required

#### Filter cartridge types:

##### **Chloramines** (FS-QC-M)

- Reduces chloramines, chlorine taste and odor, and other offensive contaminants that can adversely affect the taste of water
- Reduces possible health contaminants such as Cryptosporidium and Giardia cysts
- Sub-micron filtration reduces dirt and particles as small as 0.5 micron in size like lead, mercury, herbicides and pesticides
- Improves the taste of fountain beverages and helps retain the drink's carbonation
- Protects drink system equipment from clogging, corrosion and abrasive wear

##### **Multi-Use** (FS-QC-MU)

- Offers the same benefits of FS-QC-M
- Antimicrobial protection inhibits potential bacterial growth

##### **Ice** (FS-QC-I)

- Offers the same benefits of FS-QC-MU
- Scale inhibitor media keeps ice machines and/or coffee/tea brewers running efficiently

##### **Scale** (FS-QC-L)

- Scale inhibitor media keeps ice machines and/or coffee/tea brewers running efficiently

Our Quick Connect Series systems are specifically engineered to meet the demands of high volume, high quality foodservice operations with systems that are easy to use and maintain. Our expertise in advanced water filtration technology enables us to produce efficient and effective water filters at an unmatched value.

CONFIGURATION	MODEL	FLOW RATES	RATED CAPACITIES (Gal)	DIMENSIONS (H"xW"xD")	CARTRIDGE SET
1 Stage - Chloramine	FS-QC-M	1.7 / 1.3 / 1.0	3,000 / 4,500 / 6,750	22.25 x 4.25 x 4.50	FS-CLM-17-R
1 Stage - Multi-Use	FS-QC-MU	1.7 / 1.3 / 1.0	3,000 / 4,500 / 6,750	22.25 x 4.25 x 4.50	FS-MU-C-17-R
1 Stage - Ice	FS-QC-I	1.7 / 1.3 / 1.0	3,000 / 4,500 / 6,750	22.25 x 4.25 x 4.50	FS-ICE-17-R
1 Stage - Scale	FS-QC-L	1.7 / 1.3 / 1.0	6 months	15.25 x 4.25 x 4.50	FS-SC-10-R

### Replacement Filter Cartridges



#### Chloramine (FS-CLM-17-R)

- Reduces chloramines, chlorine taste and odor and other offensive contaminants - including cysts such as cryptosporidium and giardia - that can adversely affect the taste of beverages.



#### Multi-Use (FS-MU-C-17-R)

- Reduces chloramine and chlorine taste and odor effects as well as other offensive contaminants.
- Antimicrobial protection inhibits potential bacterial growth.
- Submicron filtration reduces dirt and particles as small as 0.5 micron in size and possible health contaminants such as cryptosporidium and giardia cysts.
- Protects drink system equipment from clogging, corrosion and abrasive wear.



#### Ice (FS-ICE-C-17-R)

- Reduces chloramine and chlorine taste and odor effects as well as other offensive contaminants.
- Scale inhibitor media keeps ice machines running efficiently.
- Antimicrobial protection inhibits potential bacterial growth.
- Submicron filtration reduces dirt and particles as small as 0.5 micron in size including related health contaminants such as cryptosporidium and giardia cysts.



#### Chloramine + Lead (FS-CLM+-17-R)

- Reduces chloramine as well as chlorine taste and odor effects that can adversely affect the taste of water.
- Reduces harmful contaminants such as Lead, Mercury, Asbestos, MTBE, and VOCs.
- Reduces possible health contaminants such as Cryptosporidium and Giardia cysts.
- Improves the taste of fountain beverages and helps retain the drink's carbonation.
- Protects drink system equipment from clogging, corrosion and abrasive wear.



#### Sediment (FS-SD-17-R)

- 5.0 micron pre-filter captures rust, sediment, and particulates that impact water quality.



#### Scale (FS-SC-10-R)

- Reduces the harmful effects of scale and scale build-up to protect pipes and equipment.

### Replacement Filter Cartridge general specifications

PRESSURE REQUIREMENTS	TEMPERATURE	DIMENSIONS*
10 - 125 psi (0.7 - 8.6 bar), non-shock	35 - 100°F (2 - 38°C)	Height - 17" (43.2 cm) Diameter - 5¼" (13.4 cm)

\* FS-SC-10-R height is 10" (25.4 cm)

CARTRIDGE	MICRON RATING	RATED CAPACITY	SERVICE FLOW RATE (GPM)
Chloramine FS-CLM-17-R	0.5	3,600 Gallons @ 1.7 gpm (13,627 Liters @ 6.43 Lpm) 5,500 Gallons @ 1.33 gpm (20,819 Liters @ 5.03 Lpm) 8,000 Gallons @ 1.0 gpm (30,283 Liters @ 3.78 Lpm)	NA
Multi-Use FS-MU-C-17-R	0.5	Chloramine 3,600 Gallons @ 1.7 GPM (13,627 Liters @ 6.4 Lpm) Chlorine 9,000 Gallons @ 1.7 GPM (34,069 Liters @ 6.4 Lpm)	NA
Ice FS-ICE-17-R	0.5	Chloramine 3,600 Gallons @ 1.7 GPM (13,627 Liters @ 6.4 Lpm) Chlorine 9,000 Gallons @ 1.7 GPM (34,069 Liters @ 6.4 Lpm)	NA
Chloramine + Lead FS-CLM+-17-R	0.5	1,340 gallons @ 1.4 gpm (5,072 liters @ 5.3 Lpm)	NA
Sediment FS-SD-17-R	5.0	NA	6.25
Scale FS-SC-10-R	NA	NA	5.0